

GROTE TRILLIANT® SMX.2

LED Worklamp

9-32V

DATA SHEET

WORK LIGHTING



Trilliant® SMX.2 | 2000 lm

Small Dimensions, Maximum Efficiency & Performance

- The performance version of our new entry-level SMX worklamp
- Powerful 2000 lm output at a power consumption of 27 W
- Field-proven 5700K CCT guarantee fatigue free working
- State of the art TIR-only lens design maximizes optical efficiency
- Constant luminance over the whole operating temperature range
- Long lifetime due to sophisticated thermal design
- Pressure-washer-safe according to IP69K
- Circuitry protected against automotive transients, DC over- and undervoltage and ESD
- Complies to EMC standard CISPR25 class 4
- Tested in accordance with ISO 14982 and EN 13309 for agricultural, forestry and construction-site machinery
- Two distinct light distributions cover all illumination needs, including an R23 compliant reversing lamp
- As an option, the SMX series is available with our new Ball Basket mounting system: Mount and adjust your lamp within seconds with a single bolt

Order no.	Light distribution	Assembly
64T31	FAR RANGE	BALL BASKET
64T41	CLOSE RANGE	BALL BASKET
64T51	R23	BALL BASKET
64T61	FAR RANGE	BRACKET
64T71	CLOSE RANGE	BRACKET
64T81	R23	BRACKET

PRODUCT SPECIFICATIONS

OPTICAL CHARACTERISTICS

Illuminance	
Calculated:	2600 lm
Instant-on (t ₀):	2220 lm
Continuous (t ₃₀):	2000 lm
Color temperature (CCT)	5700 K
Color rendering index (CRI)	70
Efficacy	72 lm/W

ELECTRICAL CHARACTERISTICS

Operating voltage range	9-32 V
Input current	1,86 A (14 V) and 0,98 A (28 V)
Inrush current	Nominal input current is not exceeded
Power consumption	27 W
Input connector	Deutsch DT
Operating temperature range	-40°C to +50°C
Reverse polarity protection	✓
Overheat protection	✓
ESD, overvoltage and transient protection	✓

MECHANICAL CHARACTERISTICS

Dimensions (HxWxD)	Bracket version: 123x94x52 mm Ball version: 120x94x52 mm
Weight	735 g (Bracket) 620 g (Ball)
Materials	Lens: UV resistant polycarbonate Housing: Aluminium powder-coated
Color	Black
IP Code	IP69K
Mounting	Pendant and pedestal
Maximum storage temperature	-55°C to +110°C
Impact and shock resistance	50 G
Vibration resistance	5 G (5-500 Hz)

APPROVALS AND CERTIFICATES

ECE	R10, R23
CE	✓
ISO 14982	✓
EN 13309	Without section 2 (testpuls 5a 24V)
ISO 7637-2	✓
ISO 16750	Without section 2 (testpuls 5a 24V)
ISO 10605	✓
ISO 11452	Section 2, 4 and 5
CISPR 25	Class 4
EN 60068	✓
ISO 20653	✓

LUMENS

2600 r	2220 i	2000 e
Raw	Instant-On	Effective



FOR MORE
INFORMATION
VISIT **GROTE.COM**

Grote Industries Europe GmbH
William-Grote-Weg 1, 94327 Bogen, Germany

europe@grote.com
Europe +49 9422 40331-0

U.S. +1.800.628.0809
Canada +1.800.268.5612

Mexico +52 818262 4412
China +86.21.5774.9633



GROTE TRILLIANT® SMX.2



LED Worklamp

9 - 32 V




DATA SHEET

WORK LIGHTING




Far Range - IsoLux (64T31 & 64T61)



Close Range - IsoLux (64T41 & 64T71)



R23 - IsoLux (64T51 & 64T81)



FOR MORE
INFORMATION
VISIT **GROTE.COM**

Grote Industries Europe GmbH
William-Grote-Weg 1, 94327 Bogen, Germany

europe@grote.com
Europe +49 9422 40331-0

U.S. +1.800.628.0809
Canada +1.800.268.5612

Mexico +52 818262 4412
China +86.21.5774.9633

Grote®