

AIRPORT CLASS BEACON

FROM GROTE



SAE
INTERNATIONAL
SAE J845™
STANDARD

ICAO/CAP168
STANDARD

12/24V
MULTI-VOLT
DESIGN

DURABLE
CONSTRUCTION


ENGINEERED TO MEET THE MOST RIGOROUS STANDARDS FOR AVIATION AND AIRPORT ENVIRONMENTS

This compact, rugged amber beacon delivers seven selectable flash patterns, including the CAP168/ICAO single-flash pattern required by the International Civil Aviation Organization. With multiple certifications and a low current draw of just 1.5A at 12 VDC, it is ideally suited for aviation-support equipment such as fuel trucks, baggage carts, de-icing vehicles, and ground service units.



79363-5

VOLTAGE: 12-24 VDC
AMPERAGE: 1.5A @ 12 VDC, 0.75A @ 24 VDC
DURABILITY RATING: IP67
OPERATING TEMPERATURE:
 -30°C (-22°F) TO 60°C (140°F)
APPROVALS: SAE J845 CLASS I, ECE R65 CLASS I, CE, UKCA, ECE R10, ECE R65 (TA1), ICAO/CAP168, MEETS CISPR 25 CLASS III



- 7 FLASH PATTERNS**
1. SINGLE FLASH (ECE R65)
 2. DOUBLE FLASH (ECE R65/SAE)
 3. QUAD FLASH (ECE R65)
 4. QUICK FLASH
 5. ROTATING FLASH
 6. ROTATING+QUAD FLASH
 7. SINGLE FLASH (CAP168/ICAO)

FEATURES & BENEFITS

- Meets CAP 168 and ICAO standards for compliant airport and aviation facility use
- Seven selectable flash patterns provide flexible signaling for multiple ground operations
- IP67-rated housing delivers reliable performance in wet, dusty, and high-vibration conditions
- Fresnel lens optics ensure 360° visibility, including from above
- Wide temperature range supports reliable operation in extreme climates

PART #	DESCRIPTION	MOUNT	COLOR
79363-5	AIRPORT CLASS LED BEACON, CLASS I	PERMANENT	● AMBER



EZ-FIND
SCAN FOR TECH SPECS,
RELATED PRODUCTS
AND MORE

**FOR MORE INFORMATION
VISIT OUR WEBSITE.
GROTE.COM**

